





Pencil Tag

This pencil tag provides protection for high-risk items unable to be secured with a pin-style hard tag. The lanyard cable contains a stainless-steel pin, which makes the tag function well and easy to use. The sleek shape will not affect the product, but provides a powerful visual deterrent that allows retailers to open merchandise with confidence.

Retailer Values

//Small, compact and lightweight, this mini-security tag is perfect for those looking for a small lightweight pencil tag. //The impact to merchandise on display is being minimized due to the small aesthetic design.

//Improving sales by promoting open merchandising

// Reducing the loss of goods and saving labor costs associated with in-store tagging, allowing store associates to offer premium service.

//Reducing waste through recycling used tags for reapplication, consistent with green concepts

//This unobtrusive, visible deterrent is a desirable option to a wide variety of merchandise

//Easy application and removal to help improve store operations

Specifications

Frequency	8.2MHz/58KHz(*)
Color	Beige or customized
Dimension	54x12x20mm
Lockthree balls	, standard/super lock
Material	ABS
Pullout Force	>400N

Note: * means available on 1.95, 1.9, 3.25, 4.75, 9.5 and other special frequency

Solution Application

Used for: Clothes, Hats, Shoes, Sporting goods etc

Application: Apparel, Shopping Arcade, General Merchandise

Product Codes

T124-RF-SDL-BGE T124-RF-SPL-BGE T124-AM-SDL-BGE T124-AM-SPL-BGE

Product Compatibility

Magnetic Detacher:

D05 & other compatible Super D04 & other compatible Standard

Lanyard:

185mm or customized

Environmental Constraints

Temperature

Maximum storage temperature not to exceed 60°C (140°F) for 96 hours at 80% RH

Humidity

Unaffected by 80% humidity at 60°C (140° F), up to 96 hours.

Packing Details

Packing Details:

1000pcs/ctn; 13.5kgs/ctn; 0.028cbm/ctn

Packing by premium carton

Shipping:

Sea Port: Ningbo or Shanghai Air Port: Hangzhou or Shanghai Lead Time: 15 Days for regular order